



**Valvola a sfera alta pressione con attacco gas (315 bar)  
Ball Valve with female thread (315 bar)**

Tavola 1 / Table 1

DESCRIZIONE DESCRIPTION	CODICE CODE	DN	PN	LW	d	L	I	H	h	m	i	K	Peso Weight (kg)
AB-I 21-32/G 1/4	97780419	6	500	6	G1/4	69	40	47	33	13,5	14	115	0,3
AB-I 21-32/G 3/8	97780420	10	500	10	G3/8	72	43	52	38	17,5	14	115	0,3
AB-I 21-32/G 1/2	97780421	16	400	15	G1/2	83	48	63	46	19	16,3	160	0,6
AB-I 21-32/G 3/4	97780422	20	315	20	G3/4	95	62	75	57	24,5	18	200	2,0
AB-I 21-32/G 1	97780423	25	315	25	G1	113	66	83	65	29,5	20	200	2,1
AB-I 21-32/G 1 1/4	97780424	32	350	32	G1 1/4	111	95	107	86	40,5	22	320	3,2
AB-I 21-32/G 1 1/2	97780425	40	350	38	G1 1/2	130	107,5	124	103	50	24	320	4,3
AB-I 21-32/G 2	97780426	50	350	48	G2	140	120	138	117	59	26	320	10
AB-I 21-32/G 1/4 + LOCK	97780427	6	500	6	G1/4	69	40	47	33	13,5	14	115	0,3
AB-I 21-32/G 3/8 + LOCK	97780428	10	500	10	G3/8	72	43	52	38	17,5	14	115	0,3
AB-I 21-32/G 1/2 + LOCK	97780429	16	400	15	G1/2	83	48	63	46	19	16,3	160	0,6
AB-I 21-32/G 3/4 + LOCK	97780430	20	315	20	G3/4	95	62	75	57	24,5	18	200	2,0
AB-I 21-32/G 1 + LOCK	97780431	25	315	25	G1	113	66	83	65	29,5	20	200	2,1
AB-I 21-32/G 1 1/4 + LOCK	97780432	32	350	32	G1 1/4	111	95	107	86	40,5	22	320	3,2
AB-I 21-32/G 1 1/2 + LOCK	97780433	40	350	38	G1 1/2	130	107,5	124	103	50	24	320	4,3
AB-I 21-32/G 2 + LOCK	97780434	50	350	48	G2	140	120	138	117	59	26	320	10

**MATERIALI:**

Corpo: Acciaio  
 Sfera: Acciaio  
 Guarnizioni di tenuta: POM  
 Tenuta albero e attacchi: Buna-N (se ...-V = Viton)  
 Leva: Fusa in zinco

**MATERIAL:**

Body: Steel  
 Ball: Steel  
 Seal: POM  
 Shaft and ports seal: Buna-N (if ...-V = Viton)  
 Handle: Zn Cast



1		<b>BOSCH REXROTH S.p.A. Cernusco S/N (MI)</b> Via G. Di Vittorio, 1 Tel. 02-923651	<i>Prep.: S. Tocchetto</i> <i>Contr.: A. Tognoli</i>
07-11-02			